

Material Safety Data Sheet

May be used to comply with OSHA's hazard communication standards 29 CFR 1910-1200

U.S. Department of Labor
Occupational Safety and Health Administration
(Non Mandatory form)
Form Approved
QMB No 1218-0072

IDENTITY ENVIRO-TEK ENGINE FLUSH

SECTION-1

Manufacture's name **Emergency telephone number**

ENVIROTEK USA (864) 641-5478

Address (Number, street, City, State, Zip Code) **Telephone number for information**

907 Vanessa Dr Boiling Springs, SC 29316 (864) 641-5478

Date Prepared: January 01, 2009

SECTION-11- Hazardous Ingredients Identity Information U.N.1992

Hazardous commodities (specific chemical identity, common names) **CAS#**

Petroleum Distillate	64741-89-5	1-80%
Petroleum Distillate	8008-20-6	1-80%
Petroleum Distillate	111-76-2	1-80%
Zinc Alkyl Dithio Phosphate	26566-95-0	0-10%
Aromatic, Aliphatic, Paraffinic Hydrocarbons		94%
Zinc Dithio Phosphate.		6%

SECTION-111 Physical/Chemical characteristics

Boiling Point: <0.0°c **Specific gravity (H20=1)** 0.8078 at 20°c

Solubility in water: Insoluble in water

Appearance and color: Clear Light Green Amber liquid.

SECTION-1V- Fire and Explosion Hazard data

Flash point: 23° to-61°c **Flammable limits:** > 0°c

Extinguishing media: Chemical foam or Carbon-Dioxide

Special fire fighting procedures: Spraying with water could spread the fire. Use water to cool heat exposed containers.

Unusual fire and extinguishing hazards: C0, C02 on combustion. HDPE plastic containers require normal fire fighting procedure for HDPE plastic.

SECTION-V Reactivity Data

Reactive: Stable X	The product is stable when contained in .12 OZ HDPE plastic containers.
Incompatibility	None known.
Hazardous Decomposition or Byproducts	None known.
Hazardous Polymerization	Will not occur.

SECTION-V1- Health Hazard Data

Points of entry:	Inhalation (Avoid)	Skin (Avoid)	Ingestion (Avoid)
Known Hazards (Acute and chronic)	Moderate irritant. Can cause headaches, nausea, dizziness.		
Carcinogenicity	Negative		
Signs and Symptoms of Exposure	Skin or eye irritation, headaches, nausea.		
Clinical conditions Aggravated by exposure.	Irritation of skin or eyes.		
Emergency and First Aid procedure:	Skin Remove clothing and flush with water.		
	Breathing Remove to well ventilated area.		
	Eyes Flush with water.		
	Ingestion. Summon Physician.		

SECTION-V11- Precautions for safe handling and use.

Steps to be taken in case material is released or spilled. Use absorbent material to soak up any product spilled, e.g. paper, wood shavings, wood pulp.

Waste Disposal Method Burn in an incinerator or landfill site disposal with local regulations.

Precautions to be taken in managing and storing Keep in a cool well ventilated area away from heat sources, sparks or flames NO smoking.

Other Precautions Avoid repeated or prolonged breathing or skin contact. If exposed wash with soap and water.

SECTION-V111- Control Measures

Respiratory Protection (Specify type) Use breathing apparatus if working with exposed product in an enclosed area.

Ventilation Local exhaust Keep well ventilated.
Mechanical (General) Spark proof.

Protective Gloves Only for prolonged contact. **Eye Protection** Wear protective glasses.

Protective Clothing or Equipment None required.

Health/Hygienic Practices Product well packed in sealed HDPE plastic bottles. There are no problems unless the container is punctured.

PACKAGING: This product is packaged and tested to the highest UPS specification to ensure the utmost safety during transportation.
